

# UNIVERGE SV9100

## COMMUNICATIONS PLATFORM

The UNIVERGE SV9100 Communications Platform is a robust, feature-rich and scalable system that is ideal for small and medium businesses. It is designed to help solve today's communications challenges and offers the ability to expand as your business grows in the future.



### UNIVERGE SV9100 AT A GLANCE

- > **Multi-carrier SIP support** - Offers greater resilience and provides more cost effective routing of calls
- > **VoIP, Traditional Voice Support and/or a combination of both** - Offers flexibility and choice to suite individual business requirements
- > **Application Integration** - Embedded applications are easily accessed through simple licence activation
- > **Scalability** - As a business's communication needs grow with the company
- > **Stackable Architecture** - The SV9100's rack stackable chassis supports server functions, media gateways and media converters through a single unit



### THE SV9100 OFFERS

## SMART COMMUNICATIONS FOR SMALL AND MEDIUM BUSINESSES



### UNIVERGE SV9100 NEW SYSTEM ENHANCEMENTS

- > Increased memory & processor upgrade
- > Security Improvements
- > Increased UC & Mobility Applications
- > New Desktop Telephones
- > Enhanced Longevity & Investment Protection

**TECHNICAL DATA**

Chassis	9.5 inch			19 inch			
Number of SV9100s	1	1	2	3	4	w/ NetLink	
<b>Outside Lines</b>	<b>IP Lines</b>						
	IP Trunks (SIP)*			400**			
	<b>Analog Trunks</b>						
	Analog Trunks (COT)	16	40	88	136	184	400
	PRI Channels	30	90	180	180	180	400
	BRI Channels	16	40	88	136	184	400
<b>Terminals</b>	<b>IP Terminals</b>						
	UNIVERGE DT800 & DT900 Series			896**			
	SP310 Soft Phone			256**			
	SIP DECT terminals			896			
	<b>Digital terminals (TDM)</b>						
	UNIVERGE DT400 & DT500 Series	32	80	160	240	320	896
	<b>Analog terminals</b>						
	SLT (-24V)	32	80	160	240	320	896
	SLT (-48V)	3	20	44	68	92	896
	<b>Applications**</b>	IP Gateway channels			256		
IP Gateway channels with sRTP			256				
<b>Embedded Applications</b>							
<i>Voicemail</i>							
VM InMail		16 channel; 40/230 hours of storage; 896 Mailboxes (896 subscribers, 32 groups, 32 call routing mailboxes)					
VRS channels		16 channel					
InACD		(896 Agents, 64 ACD Groups)					
<b>InApps (Built-in applications)</b>		InGuard (Toll Fraud Defence), InHotel (Property Management System), InReports (Call Management), InUC (Unified Communications)					
<b>In-Skin Applications</b>							
Gigabit POE switch		8 ports per blade					
<b>Networking</b>							
NetLink networking #		50 systems					
FeatureNet (AspireNet)		50 systems					
K-CCIS networking		50 systems					
<b>Physical characteristics</b>		SV9100 chassis dimensions	115 x 220 x 369 mm (hxwxd)		88 x 430 x 390 mm (hxwxd)		
	Empty chassis weight	2.15 Kg	6.35 Kg; Average weight of cards 275 g (maximum 6 cards in chassis)				
<b>Power consumption</b>	SV9100 Chassis Power Rating	Input 100V/120V/220V/230-240V - 2.43A/2.19A/1.19A/1.15A 50/60Hz					
<b>Compliance</b>	The SV9100 Communications Server carries a CE mark and complies with:						
	EMC	EN55032 Emission, EN55024 Immunity, EN61000 Powering					
	Safety	EN60950-1					
	Transmission and signalling	TBR3, TBR4, ES203-021, TBR8, TBR38					

\* Maximum number of simultaneous calls is limited by the Voice over IP Resources (IP Pad Channels) available  
 \*\* Maximum number based on peer to peer, maximum independent of chassis configuration

NEC and the NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All trademarks identified with © or TM are registered trademarks or trademarks of their respective owners. Models may vary for each country, and due to continuous improvements this specification is subject to change without notice. Please refer to your local NEC representative(s) for further details.

**Corporate Headquarters (Japan)**  
 NEC Corporation  
[www.nec.com/univerge](http://www.nec.com/univerge)

For further information please contact NEC Corporation or: